## **Material Safety Data Sheet**

Product Name:GREEN LAWNGERProduct Code:BUI/GL

**HMIS Codes:** H F R P 1 1 0 X

#### Section I – Manufacturer Identification

Manufacturer's Name:Becker Underwood, Inc.Emergency Phone:Chemtrec (800) 424-9300Prepared By:MSDS Coordinator

 Address:
 P.O. Box 667, 801 Dayton Ave., Ames, IA 50010

 Information Phone:
 (515) 232-5907

 Date Revised:
 July 21, 2004

# Section II – Ingredients and Hazards

Ingredient Name	Occupational Exposure Limits				
Ingredient	CAS Number	OSHA - PEL	ACGIH - TLV	Wt. Percent	
Kaolin*	1332-58-7	15 mg/m <sup>3</sup> (Total dust)	2 mg/m <sup>3</sup> (Respirable fraction)	0-10 %	
		$5 \text{ mg/m}^3$ (Respirable dust)			

\*\*\*No reportable quantities of toxic chemical(s) subject to the reporting requirements of Section 313 of SARA Title III and of 40 CFR 372 are present\*\*\*

\*The occupational exposure limits for Kaolin apply to dried product only.

#### Section III - Physical/Chemical Characteristics

Boiling Point:	NE	Specific Gravity: (H <sub>2</sub> 0 = 1):	1.0-1.2
Vapor Density:	Heavier than air	Evaporation Rate:	Slower than ether
Solubility In Water:	Soluble	Appearance and Odor:	Dark green liquid, mild odor

## Section IV - Fire and Explosion Hazard Data:

Flash Point:NAMethod Used:NAFlammable Limits in Air by Volume:NALower:NAUpper:NAExtinguishing Media:Foam, alcohol foam, CO2, dry chemical, water fog

**Fire Fighting Precautions & Hazards:** Fire fighters should wear butyl rubber boots, gloves, and body suit and a NIOSH/MSHA self-contained breathing apparatus.

**Unusual Fire and Explosion Hazards:** Not a fire or explosion hazard when stored under normal conditions.

## Section V – Reactivity Data

Stability: Stable

**Conditions to Avoid:** Extremes in temperature. High humidity.

**Incompatibility (Materials to Avoid):** Long term storage in direct contact with reactive metals such as aluminum, zinc, copper, nickel, magnesium, etc. Other materials to avoid include strong oxidizing agents.

**Hazardous Decomposition Products:** When involved in a fire, burning may evolve noxious fumes which may include carbon monoxide, carbon dioxide, nitrous oxides, acetic acid, or other toxic compounds depending on the chemical composition and combustion conditions. However, all of the water must be driven off first for this to occur. **Hazardous Polymerization:** Will not occur.

## **Section VI - Health Hazard Data**

Inhalation Health Risks and Symptoms of Exposure: Prolonged inhalation may lead to respiratory tract irritation.

Skin and Eye Contact Health Risks and Symptoms of Exposure: Prolonged or repeated contact may result in mechanical irritation.

Skin Absorption Health risks and Symptoms of Exposure: None expected.

## Section VI - Health Hazard Data (Continued)

Ingestion Health Risks and Symptoms of Exposure: Health Hazards (acute and chronic): None known.

ACGIH? Carcinogenicity No IARC Monographs?

**Existing Medical Conditions Generally Aggravated By Exposure:** May provoke asthmatic response in persons with asthma who are sensitive to airway irritants.

#### **Emergency and First Aid Procedures:**

Eves: Flush with flowing water for at least 15 minutes. Call a physician.

Skin: Wash affected area with soap and water. If irritation develops consult a physician. Remove and launder contaminated clothing before reuse.

If difficulty in breathing occurs, move to fresh air. Get immediate medical attention. Inhalation:

**Ingestion:** Get immediate medical attention. Unless advised otherwise, dilute with water or milk.

## Section VII – Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled: Contain the spill to prevent a large discharge to surface streams or storm sewers. An absorbent material would aid in cleaning up a liquid spill. If liquid cleanup is necessary, collect in drums, buckets, or other containers.

Waste Disposal Method: The environmental concern is discoloration of land or water. Disposal must be made in accordance with federal, state, and local regulation.

Precautions to be Taken in Handling and Storing: Local exhaust. Do not freeze. Avoid unnecessary skin contact. Do not breathe fumes.

Eve wash fountains should be easily accessible. As with all chemicals, keep out of the reach of Other Precautions: children.

## **Section VIII - Control Measures**

If excessive vapors or mists are generated, wear NIOSH/MSHA approved organic vapor/mist respirator. Respiratory: Ventilation: Use local exhaust to control excessive vapors/mists. If applicable, proper personal protection is a NIOSH/MSHA approved respirator.

Gloves, coveralls, apron, boots as necessary to prevent skin contact as needed. Clothing:

**Eye:** Chemical goggles; wear face shield if splashing hazard exists.

Open wounds or skin surface disruptions should be covered with a chemical resistant patch to minimize Other: absorption risks. Clean clothing should be worn daily to avoid possible long-term build up of the product leading to chronic overexposure.

## Section IX - Shipping and Labeling Information

D.O.T. Shipping Data: Not regulated. D.O.T. Hazard Classification NA D.O.T. Labels Required: NA D.O.T. Identification NA

## **Section X - Disclaimer**

The opinions expressed herein are those of qualified persons with Becker Underwood, Inc. We believe the information contained here is current as of the date of this Material Safety Data Sheet. Since the use of this product is not within the control of Becker Underwood, Inc., it is the user's obligation to determine a safe end use of this product.

Ingestion of large quantities may be harmful.

No