acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015

Printing date 10/20/2015

Reviewed on 10/20/2015

1 Identification

- · Product identifier
- · Trade name: UDAP Pepper Power OC, Fog
- Product size: 4oz. (11g) / .7oz. (20g) / 1.9oz. (50g) / 3.1oz (90g) / 6.3oz. (180g)
- · Recommended use and restriction on use
- · Recommended use: Animal deterrent device.
- · Restrictions on use: Contact manufacturer.
- · Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

UDAP Industries, Inc

1703 Waterline Road

Butte, MT 59701

Telephone Number for Information/Customer Care: 1-866-232-7911

• Emergency telephone number: Infotrac Emergency Hotline: 1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

· Additional information:

There are no other hazards not otherwise classified that have been identified.

0 % of the mixture consists of component(s) of unknown toxicity.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:





GHS04 GHS07

- · Signal word: Warning
- · Hazard-determining components of labeling:

Oleoresin Capsicum

Hazard statements:

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

(Cont'd. on page 2)

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015

Printing date 10/20/2015 Reviewed on 10/20/2015

Trade name: UDAP Pepper Power OC, Fog

(Cont'd. of page 1)

H319 Causes serious eve irritation. H335 May cause respiratory irritation.

· Precautionary statements:

P261 Avoid breathing mist/vapors/spray. P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection / face protection.

Use only outdoors or in a well-ventilated area. P271

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

IF ON SKIN: Wash with plenty of water. P302+P352

IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340

Call a POISON CENTER/doctor if you feel unwell. P312 P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. P362+P364

P405 Store locked up. P410 Protect from sunlight.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

· Classification system

NFPA ratings (scale 0 - 4)



Health = 1Fire = 3Reactivity = 1

· HMIS-ratings (scale 0 - 4)



1 Health = 1 3 Fire = 3 REACTIVITY 1 Reactivity = 1

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerou	· Dangerous components:					
811-97-2	Norflurane	Press. Gas, H280 Simple Asphyxiant	50-100%			
112-34-5	2-(2-butoxyethoxy)ethanol	◆ Eye Irrit. 2, H319	10-25%			
8023-77-6	Oleoresin Capsicum	Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315	2,5-10%			

· Additional information:

Equivalent to 1.3% major capsaicinoid (MC) content.

(Cont'd. on page 3)

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015

Printing date 10/20/2015 Reviewed on 10/20/2015

Trade name: UDAP Pepper Power OC, Fog

(Cont'd. of page 2)

For the listed ingredient(s), the identity and exact percentage(s) are being withheld as a trade secret.

4 First-aid measures

- Description of first aid measures
- · General information: Take affected persons out into the fresh air.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

· After eve contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

- · Information for doctor
- · Most important symptoms and effects, both acute and delayed:

Coughing

Dizziness

Irritant to skin and mucous membranes.

Irritant to eyes.

May cause respiratory irritation.

Gastric or intestinal disorders when ingested.

- · Danger: No relevant information available.
- · Indication of any immediate medical attention and special treatment needed:

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · For safety reasons unsuitable extinguishing agents: None.
- · Special hazards arising from the substance or mixture

Danger of receptacles bursting because of high vapor pressure if heated.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information: Use large quantities of foam as it is partially destroyed by the product.

(Cont'd. on page 4)

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015

Printing date 10/20/2015 Reviewed on 10/20/2015

Trade name: UDAP Pepper Power OC, Fog

(Cont'd. of page 3)

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures:

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

For large spills, wear protective clothing.

Ensure adequate ventilation.

- · Environmental precautions: No special measures required.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Send for recovery or disposal in suitable receptacles.

· Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling
- · Precautions for safe handling:

Use only in well ventilated areas.

Avoid splashes or spray in enclosed areas.

· Information about protection against explosions and fires:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 120 °F / 49 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

- · Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

· Specific end use(s): No relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- Control parameters
- · Components with limit values that require monitoring at the workplace:

811-97-2 Norflurane

WEEL (USA) Long-term value: 1000 ppm

(Cont'd. on page 5)

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015

Printing date 10/20/2015 Reviewed on 10/20/2015

Trade name: UDAP Pepper Power OC, Fog

(Cont'd. of page 4)

112-34-5 2-(2-butoxyethoxy)ethanol

TLV (USA) Long-term value: 67.5* mg/m³, 10* ppm

*Inhalable fraction and vapor

- · Exposure controls
- · Engineering measures Provide adequate ventilation.
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- · Engineering controls: No relevant information available.
- · Breathing equipment: Use suitable respiratory protective device when high concentrations are present.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment No relevant information available.

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General information
- · Appearance:

Form: Aerosol

Color: According to product specification

· Odor: Pungent

· Odor threshold: Not determined.

(Cont'd. on page 6)

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015

Printing date 10/20/2015 Reviewed on 10/20/2015

Trade name: UDAP Pepper Power OC, Fog

		(Cont'd. of page 5
· pH-value:	Not determined.	
 Change in condition: Melting point/Melting range: Boiling point/Boiling range: 	Not determined. Not applicable, as aerosol.	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	
· Auto-ignition temperature:	Not determined.	
· Decomposition temperature:	Not determined.	
• Auto igniting: Product is not self-igniting.		
• Danger of explosion: Product does not present an explosion hazard.		
· Explosion limits: Lower: Upper:	Not determined. Not determined.	
· Vapor pressure:	Not determined.	
Density:Relative density:Vapor density:Evaporation rate:	elative density: Appr density: Not determined.	
 Solubility in / Miscibility with: Water: 	Fully miscible.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
 Viscosity: Dynamic: Kinematic: Other information 	ynamic: Not determined. inematic: Not determined.	

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability:
- · Thermal decomposition / conditions to be avoided:

Danger of receptacles bursting because of high vapor pressure if heated.

- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No relevant information available.
- · Incompatible materials: No relevant information available.
- · Hazardous decomposition products: Possible in traces.

(Cont'd. on page 7)

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015

Printing date 10/20/2015 Reviewed on 10/20/2015

Trade name: UDAP Pepper Power OC, Fog

(Cont'd. of page 6)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

8023-77-6 Oleoresin Capsicum

Oral LD50 3000 mg/kg (rat)

Dermal LD50 >2500 mg/kg (mouse)

- Primary irritant effect:
- · On the skin: Irritant to skin and mucous membranes.
- · On the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Subacute to chronic toxicity: No relevant information available.
- · Additional toxicological information:

Irritant

Asphyxiant gas.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Inhalation.

Eve contact.

Skin contact.

· Acute effects (acute toxicity, irritation and corrosivity):

Irritating to eyes.

Irritating to respiratory system.

Irritating to skin.

- · Repeated dose toxicity: No relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: May cause respiratory irritation.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No relevant information available.
- · Persistence and degradability: No relevant information available.

(Cont'd. on page 8)

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015

Printing date 10/20/2015 Reviewed on 10/20/2015

Trade name: UDAP Pepper Power OC, Fog

(Cont'd. of page 7)

- · Behavior in environmental systems
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- Additional ecological information
- · General notes:

Negative ecological effects are, according to the current state of knowledge, not expected.

· Other adverse effects: No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- · Uncleaned packagings
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14	ransport	information

	ι	11	V٠	-N	lu	ım	b	е	r
--	---	----	----	----	----	----	---	---	---

· DOT, ADR, IMDG, IATA UN1950

· UN proper shipping name

DOT, IMDGADRAEROSOLS1950 AEROSOLS

· IATA AEROSOLS, non-flammable

- Transport hazard class(es)
- · DOT



· Class 2.2 · Label 2.2

· ADR



• Class 2.2 5A

(Cont'd. on page 9)

acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015

Printing date 10/20/2015 Reviewed on 10/20/2015

Trade name: UDAP Pepper Power OC, Fog

	(Cont'd. of page
· Label	2.2
· IMDG, IATA	
· Class	2.2
· Label	2.2
· Packing group · DOT, ADR, IMDG, IATA	II
Environmental hazardsMarine pollutant:	No
· Special precautions for user	Not applicable.
Danger code (Kemler):	20
· EMS Number:	F-D,S-U
 Transport in bulk according to Annex MARPOL73/78 and the IBC Code 	I II of Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
· ADR	
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· IMDG	
Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation"	UN 1950 AEROSOLS, 2.2

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 304 (emergency release notification):

None of the ingredients are listed.

(Cont'd. on page 10)

(Cont'd. of page 9)

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015

Printing date 10/20/2015 Reviewed on 10/20/2015

Trade name: UDAP Pepper Power OC, Fog

· Sections 311/312 (hazardous chemical threshold planning quantity in pounds):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

· Proposition 65 (California)

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH):

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· Canadian substance listings

· Canadian Domestic Substances List (DSL):

All ingredients are listed.

Canadian Ingredient Disclosure list (limit 0.1%):

None of the ingredients are listed.

· Canadian Ingredient Disclosure list (limit 1%):

112-34-5 2-(2-butoxyethoxy)ethanol

57-55-6 Propylene Glycol

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015

Printing date 10/20/2015 Reviewed on 10/20/2015

Trade name: UDAP Pepper Power OC, Fog

(Cont'd. of page 10)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Date of preparation / last revision 10/20/2015 / -
- · Abbreviations and acronyms:

Press. Gas: Gases under pressure: Compressed gas Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com