Scroll down for all Safety Data Sheets (SDS) for this product.

Total Enclosures: 2



Cover Page for Safety Data Sheet

Thank you for choosing CHEMetrics, Inc. We appreciate your business. In order to best serve your needs for accurate and complete Safety Data, we offer the following information as supplemental to the attached SDS.

SDS No.: R6902

Version No.: 1.5

Product Name: Nitrate CHEMets® & Vacu-vials® Ampoules, Nitrite CHEMets® & VACUettes® Refills and Vacu-vials® Ampoules

Part Nos.: R-6902 Ampoules, K-6903 Ampoules, R-6904 Ampoules, R-6905 Ampoules, R-6909 Ampoules, K-6913 Ampoules, K-6923 Ampoules, K-6933 Ampoules, R-7002A, R-7002B, R-7002C, R-7002D, K-7003 Ampoules

Product Descriptions:

CHEMets Refills: Sealed glass ampoules, 7 mm OD, for visual colorimetric water analysis. Each CHEMet[™] ampoule contains approximately 0.25 mL of liquid reagent sealed under vacuum. Refills contain 30 ampoules, test kits contain 1 refill.

VACUettes Refills: Sealed glass ampoules, 7 mm OD, with small glass capillary attached, for visual colorimetric water analysis. Each VACUette[™] ampoule contains approximately 0.25 mL of liquid reagent sealed under vacuum. Refills contain 30 ampoules, test kits contain 1 refill.

Vacu-vials Ampoules: Sealed glass ampoules, 13 mm OD, for instrumental colorimetric water analysis. Each Vacu-vial[™] ampoule contains approximately 0.9 mL of liquid reagent sealed under vacuum. Test kits contain 30 ampoules.

Addendum to Section 14 Transport Information:

Shipping container markings and labels for this product, as received, may vary from the contents of section 14 of the SDS for one or both of the following reasons:

- CHEMetrics has packaged this product as Dangerous Goods in Excepted Quantities according to IATA, US DOT, and IMDG regulations.
- CHEMetrics has packaged this product as part of a test kit or reagent set composed of various chemical reagents and elected to ship as UN 3316 Chemical Kit, Hazard Class 9, Packing Group II or III.

In case of reshipment, it is the responsibility of the shipper to determine appropriate labels and markings in accordance with applicable transportation regulations.

Additional Information:

- "Print Date" = Revision Date (expressed as DD/MM/YYY)
- Test kits and reagents sets may contain additional chemical reagents. See separate SDS(s).

CHEMets®, VACUettes®, Vacu-vials®, and Titrets® are registered trademarks of CHEMetrics Inc.

4295 Catlett Road, Midland, VA 22728 • P: 800.356.3072 • F: 540.788.4856 • www.chemetrics.com



Nitrate CHEMets & Vacu-vials Ampoules, Nitrite CHEMets & VACUettes Refills and Vacu-vials Ampoules

CHEMetrics, Inc.

Chemwatch: 9-101476 SDS No: R6902 Version No: 1.5 Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 2

Issue Date: **25/02/2015** Print Date: **12/03/2015** Initial Date: **25/11/2014** S.GHS.USA.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Nitrate CHEMets & Vacu-vials Ampoules, Nitrite CHEMets & VACUettes Refills and Vacu-vials Ampoules
Synonyms	Part Nos.: R-6902 Ampoules, K-6903 Ampoules, R-6904 Ampoules, R-6905 Ampoules, R-6909 Ampoules. K-6913 Ampoules, K-6923 Ampoules, K-6933 Ampoules, R-7002, R-7002B, R-7002D, K-7003 Ampoules
Proper shipping name	Not Applicable
Chemical formula	Not Applicable
Other means of identification	Not Available
CAS number	Not Applicable

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Component of water analysis test kits K-6903, K-6904, K-6905, K-6909A, K-6909B, K-6909C, K-6909D, K-6913, K-6923, K-6933, K-7003, K-7004, K-7004A,
	K-7004B, K-7004C, K-7004D

Details of the manufacturer/importer

Registered company name	CHEMetrics, Inc.
Address	4295 Catlett Road, Midland, VA. 22728 United States
Telephone	1-540-788-9026
Fax	1-540-788-4856
Website	www.chemetrics.com
Email	technical@chemetrics.com

Emergency telephone number

• • •	
Association / Organisation	ChemTel Inc.
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	+01-813-248-0585

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

GHS Classification	Acute Aquatic Hazard Category 3, Skin Sensitizer Category 1		
Label elements			
GHS label elements			
SIGNAL WORD	WARNING		
Hazard statement(s)			
H317	May cause an allergic skin reaction		
H320	Causes eye irritation		
H402	Harmful to aquatic life		

Page 2 of 9

Nitrate CHEMets & Vacu-vials Ampoules, Nitrite CHEMets & VACUettes Refills and Vacu-vials Ampoules

Precautionary statement(s) Prevention

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s) Response

P302+P352	IF ON SKIN: Wash with plenty of water and soap
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
7732-18-5	>81	water
107-21-1	10	ethylene glycol
67-63-0	3	isopropanol
123333-70-0	2	sulfanilic acid, sodium salt
490-79-9	1	gentisic acid
5808-22-0	1	chromotropic acid disodium salt dihydrate
63451-33-2	<1	CDTA, disodium magnesium salt
Not Available	<0.1	Proprietary ingredients

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Immediately remove all contaminate area around burn. Immediately removes a for the use of cold packs and topical antibiotics. Immediately removes all cont cold) running water or immerse in cool water until pain subsides. Immediately removes all cont cold) running water or immerse in cool water until pain subsides. Immediately the or control cont cold) running water or immerse in cool water until pain subsides. Immediately the or control cont cold) running water or immerse in cool water until pain subsides. Immediately removes all contends, the max cause infection. Immediately removes all contends, the max cause infection. Immediately represented the subside removes and topical antibiotics. Immediately removes all contends are in the available. Immediately removes all contaming water is not available. Immediately removes and running water for 10-15 minutes. Immediately removes all contaming water is not available. Immediately removes and running water for 10-15 minutes. Immediately removes are ply butter or ointments; this may cause infection. Immediately removes are proven to the remove and cause further damage. Immediately removes are presented and secure in place with gauze or tape. Immediately removes and topical and each and each and each are explored and each and each and each are explored a

Ampoules

	 Seek immediate medical or emergency assistance. In the mean time: Protect burn area cover loosely with sterile, nonstick bandage or, for large areas, a sheet or other material that will not leave lint in wound. Separate burned toes and fingers with dry, sterile dressings. Do not soak burn in water or apply ointments or butter; this may cause infection. To prevent shock see above. For an airway burn, do not place pillow under the person's head when the person is lying down. This can close the airway. Have a person with a facial burn sit up. Check pulse and breathing to monitor for shock until emergency help arrives.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically

- To treat poisoning by the higher aliphatic alcohols (up to C7):
- Gastric lavage with copious amounts of water
- It may be beneficial to instill 60 ml of mineral oil into the stomach.
- Oxygen and artificial respiration as needed.
- Electrolyte balance: it may be useful to start 500 ml. M/6 sodium bicarbonate intravenously but maintain a cautious and conservative attitude toward electrolyte replacement unless shock or severe acidosis threatens
- To protect the liver, maintain carbohydrate intake by intravenous infusions of glucose.
- Haemodialysis if coma is deep and persistent. [GOSSELIN, SMITH HODGE: Clinical Toxicology of Commercial Products, Ed 5)

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for shock.
- Monitor and treat, where necessary, for pulmonary oedema. Anticipate and treat, where necessary, for seizures.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- Give activated charcoal.

ADVANCED TREATMENT

- · Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- If the patient is hypoglycaemic (decreased or loss of consciousness, tachycardia, pallor, dilated pupils, diaphoresis and/or dextrose strip or glucometer readings below 50 mg), give 50% dextrose
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

- Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- Acidosis may respond to hyperventilation and bicarbonate therapy.
- Haemodialysis might be considered in patients with severe intoxication.
- Consult a toxicologist as necessary. BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

For C8 alcohols and above

Symptomatic and supportive therapy is advised in managing patients.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

	The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.
	Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible
	substances.
	In such an event consider:
	▶ foam.
	▶ dry chemical powder.
Special hazards arising fro	om the substrate or mixture
Fire Incompatibility	None known.

Advice	for	firefighters	

 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. **Fire Fighting** Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area.

Page 4 of 9

Nitrate CHEMets & Vacu-vials Ampoules, Nitrite CHEMets & VACUettes Refills and Vacu-vials
Ampoules

	DO NOT approach containers suspected to be hot.
Fire/Explosion Hazard	 The material is not readily combustible under normal conditions. However, it will break down under fire conditions and the organic component may burn. Not considered to be a significant fire risk. Heat may cause expansion or decomposition with violent rupture of containers. Decomposes on heating and may produce toxic fumes of carbon monoxide (CO).

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up.
Major Spills	Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course.
	Personal Protective Equipment advice is contained in Section 8 of the MSDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	 DO NOT allow clothing wet with material to stay in contact with skin Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. Wear impact- and splash-resistant eyewear. Break the ampoule tip only when it is immersed in sample. Breaking the tip in air may cause the glass ampoule to shatter
Other information	For optimum analytical performance, store in the dark and at room temperature.

Conditions for safe storage, including any incompatibilities

Suitable container	 Glass container is suitable for laboratory quantities Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	 Glycols and their ethers undergo violent decomposition in contact with 70% perchloric acid. This seems likely to involve formation of the glycol perchlorate esters (after scission of ethers) which are explosive, those of ethylene glycol and 3-chloro-1,2-propanediol being more powerful than glyceryl nitrate, and the former so sensitive that it explodes on addition of water. Alcohols are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents. reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzincs, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium should not be heated above 49 deg. C. when in contact with aluminium equipment Ethylene glycol: reacts violently with oxidisers and oxidising acids, sulfuric acid, chlorosulfonic acid, chromyl chloride, perchloric acid forms explosive mixtures with sodium perchlorate is incompatible with strong acids, caustics, aliphatic amines, isocyanates, chlorosulfonic acid, oleum, potassium bichromate, phosphorus pentasulfide, sodium chlorite

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US ACGIH Threshold Limit Values (TLV)	ethylene glycol	‡ Ethylene glycol	Not Available	Not Available	100 mg/m3	TLV® Basis: URT & eye irr
US NIOSH Recommended Exposure Limits (RELs)	ethylene glycol	1,2-Dihydroxyethane; 1,2-Ethanediol; Glycol; Glycol alcohol; Monoethylene glycol	Not Available	Not Available	Not Available	See Appendix D
US OSHA Permissible Exposure Levels (PELs) - Table Z1	isopropanol	Isopropyl alcohol	980 mg/m3 / 400 ppm	Not Available	Not Available	Not Available

Nitrate CHEMets & Vacu-vials Ampoules, Nitrite CHEMets & VACUettes Refills and Vacu-vials Ampoules

US ACGIH Threshold Limit Values (TLV)	isopropanol	2-Propanol	200 ppm	400 ppm	Not Available	TLV® Basis: Eye & URT irr; CNS impair; BEI
US NIOSH Recommended Exposure Limits (RELs)	isopropanol	Dimethyl carbinol, IPA, Isopropanol, 2-Propanol, sec-Propyl alcohol, Rubbing alcohol	980 mg/m3 / 400 ppm	1225 mg/m3 / 500 ppm	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
ethylene glycol	Ethylene glycol	10 ppm	40 ppm	60 ppm
isopropanol	Isopropyl alcohol	400 ppm	400 ppm	12000 ppm
chromotropic acid disodium salt dihydrate	Dihydroxynaphthalene-2,7-disulfonic acid, disodium salt dihydrate, 4,5-	30 mg/m3	330 mg/m3	2000 mg/m3

Ingredient	Original IDLH	Revised IDLH
water	Not Available	Not Available
ethylene glycol	Not Available	Not Available
isopropanol	12,000 ppm	2,000 [LEL] ppm
sulfanilic acid, sodium salt	Not Available	Not Available
gentisic acid	Not Available	Not Available
chromotropic acid disodium salt dihydrate	Not Available	Not Available
CDTA, disodium magnesium salt	Not Available	Not Available
Proprietary ingredients	Not Available	Not Available

Exposure controls

	Enclosed local exhaust ventilation is required at points of dust, fume or vapour generation.
	HEPA terminated local exhaust ventilation should be considered at point of generation of dust, fumes or vapours.
Appropriate engineering controls	Barrier protection or laminar flow cabinets should be considered for laboratory scale handling.
	A fume hood or vented balance enclosure is recommended for weighing/ transferring quantities exceeding 500 mg.
	When handling quantities up to 500 gram in either a standard laboratory with general dilution ventilation (e.g. 6-12 air changes per hour) is preferred.
Personal protection	
Eye and face protection	 When handling very small quantities of the material eye protection may not be required. For laboratory, larger scale or bulk handling or where regular exposure in an occupational setting occurs: Chemical goggles. Face shield. Full face shield may be required for supplementary but never for primary protection of eyes. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.
Skin protection	See Hand protection below
Hands/feet protection	 NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Body protection	See Other protection below
Other protection	 For quantities up to 500 grams a laboratory coat may be suitable. For quantities up to 1 kilogram a disposable laboratory coat or coverall of low permeability is recommended. Coveralls should be buttoned at collar and cuffs. For quantities over 1 kilogram and manufacturing operations, wear disposable coverall of low permeability and disposable shoe covers. For manufacturing operations, air-supplied full body suits may be required for the provision of advanced respiratory protection.
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index". The effect(s) of the following substance(s) are taken into account in the *computer*generated selection: Nitrate CHEMets & Vacu-vials Ampoules, Nitrite CHEMets & VACUettes Refills and

Vacu-vials Ampoules

Material	СРІ
NEOPRENE	A
BUTYL	С
NAT+NEOPR+NITRILE	С

Respiratory protection

Type BAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	Air-line*	BAX-2 P2	BAX-PAPR-2 P2 ^
up to 20 x ES	-	BAX-3 P2	-
20+ x ES	-	Air-line**	-

Page 6 of 9

Nitrate CHEMets & Vacu-vials Ampoules, Nitrite CHEMets & VACUettes Refills and Vacu-vials Ampoules

NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE/NATURAL	С
NITRILE	С
NITRILE+PVC	С
PE/EVAL/PE	С
PVA	С
PVC	С
TEFLON	С
VITON	С

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final

selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as

"feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Brownish yellow to gold		
Physical state	Liquid	Relative density (Water = 1)	1.01
Odour	Odourless	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	3.5	Decomposition temperature	Not Available
Melting point / freezing point (°C)	-2	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	125	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Inhaled

Information on toxicological effects

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Not normally a hazard due to non-volatile nature of product

Aliphatic alcohols with more than 3-carbons cause headache, dizziness, drowsiness, muscle weakness and delirium, central depression, coma, seizures and behavioural changes. Secondary respiratory depression and failure, as well as low blood pressure and irregular heart rhythms, may follow.

^ - Full-face

 $\begin{array}{l} \mathsf{A}(\mathsf{All classes}) = \mathsf{Organic vapours}, \mathsf{B} \ \mathsf{AUS or B1} = \mathsf{Acid gasses}, \mathsf{B2} = \mathsf{Acid gas or hydrogen} \\ \mathsf{cyanide}(\mathsf{HCN}), \mathsf{B3} = \mathsf{Acid gas or hydrogen cyanide}(\mathsf{HCN}), \mathsf{E} = \mathsf{Sulfur dioxide}(\mathsf{SO2}), \mathsf{G} = \\ \mathsf{Agricultural chemicals}, \mathsf{K} = \mathsf{Ammonia}(\mathsf{NH3}), \mathsf{Hg} = \mathsf{Mercury}, \mathsf{NO} = \mathsf{Oxides of nitrogen}, \mathsf{MB} = \\ \mathsf{Methyl bromide}, \mathsf{AX} = \mathsf{Low boiling point organic compounds}(\mathsf{below 65 degC}) \end{array}$

		Ampoul	les		
Ingestion	Overexposure to delirium and cor The material has animal or humar for ethylene glyc Ingestion sympto	o non-ring alcohols causes nervous system sy na. s NOT been classified by EC Directives or oth e evidence. sol: oms include respiratory failure, central nervou:	mptoms. These include headache, r her classification systems as "harmf s depression, cardiovascular collaps	nuscle weakness ful by ingestion". e, pulmonary oed	s and inco-ordination, giddiness, confusion, This is because of the lack of corroborating dema, acute kidney failure, and even brain
Skin Contact	damage. The material is r Nevertheless, gr Most liquid alcol Open cuts, abra Entry into the blo	not thought to produce adverse health effects cod hygiene practice requires that exposure b nols appear to act as primary skin irritants in h ded or irritated skin should not be exposed to cod-stream, through, for example, cuts, abrasi	or skin irritation following contact (a e kept to a minimum and that suitab numans. Significant percutaneous al this material ions or lesions, may produce system	is classified by E le gloves be used bsorption occurs hic injury with hard	C Directives using animal models). d in an occupational setting. in rabbits but not apparently in man. mful effects.
Eye	Although the liqu by tearing or cor Isopropanol vap may cause teari	id is not thought to be an irritant (as classifier njunctival redness (as with windburn). our may cause mild eye irritation at 400 ppm. \$ ng or blurring of vision.	d by EC Directives), direct contact w Splashes may cause severe eye irrit	<i>i</i> ith the eye may ation, possible co	produce transient discomfort characterised rneal burns and eye damage. Eye contact
Chronic	Skin contact with Substance accur There is some e There is some e	n the material is more likely to cause a sensitis mulation, in the human body, may occur and m vidence that inhaling this product is more likel vidence from animal testing that exposure to t	sation reaction in some persons com nay cause some concern following re ly to cause a sensitisation reaction ir his material may result in toxic effect	ppared to the gen epeated or long-te n some persons o s to the unborn b	eral population. erm occupational exposure. compared to the general population. aby.
	Exposure to ethy	lene glycol over a period of several weeks ma	y cause throat irritation, mild headac	he and low backa	ache.
Nitrate CHEMets &					
Vacu-vials Ampoules, Nitrite CHEMets & VACUettes Refills and Vacu-vials Ampoules	TOXICITY		IRRITATION		
Nitrate CHEMets & Vacu-vials Ampoules, Nitrite CHEMets & VACUettes Befills and	ΤΟΧΙΟΙΤΥ		IRRITATION		
Vacuerties Refills and Vacu-vials Ampoules					
ETHYLENE GLYCOL	For ethylene g Ethylene glyca respiratory tra water. In most dehydrogenas [Estimated Le	glycol: ol is quickly and extensively absorbed through ct; dermal absorption is apparently slow. Follo mammalian species, including humans, ethy se to form glycolaldehyde, which is rapidly conv thal Dose (human) 100 ml; RTECS quoted by	n the gastrointestinal tract. Limited in owing absorption, ethylene glycol is lene glycol is initially metabolised by verted to glycolic acid and glycxal by y Orica] Substance is reproductive e	oformation sugge distributed throug alcohol. aldehyde oxidase effector in rats (bi	sts that it is also absorbed through the ghout the body according to total body e and aldehyde dehydrogenase. irth defects). Mutagenic to rat cells.
ISOPROPANOL	Isopropanol is central nervou common parti	irritating to the eyes, nose and throat but gen is system and drowsiness. Few have reported cularly among alcoholics or suicide victims ar	erally not to the skin. Prolonged high I skin irritation. It can be absorbed fro nd also leads to fainting, breathing o	n dose exposure form the skin or wh lifficulty, nausea,	may also produce depression of the en inhaled. Intentional swallowing is vomiting and headache.
Nitrate CHEMets & Vacu-vials Ampoules, Nitrite CHEMets & VACUettes Refills and Vacu-vials Ampoules, SULFANILIC ACID, SODIUM SALT, GENTISIC ACID, CHROMOTROPIC ACID DISODIUM SALT DIHYDRATE	The following Contact allerg involves a cell mediated imm and the oppor	information refers to contact allergens as a g ies quickly manifest themselves as contact ec -mediated (T lymphocytes) immune reaction o une reactions. The significance of the contac tunities for contact with it are equally importar	roup and may not be specific to this czema, more rarely as urticaria or Q of the delayed type. Other allergic sk t allergen is not simply determined b t.	product. uincke's oedema in reactions, e.g. y its sensitisatior	. The pathogenesis of contact eczema contact urticaria, involve antibody- n potential: the distribution of the substance
WATER, CDTA, DISODIUM MAGNESIUM SALT	No significant	acute toxicological data identified in literature	e search.		
A	0		A	0	
Acute Toxicity	0		Carcinogenicity	0	
Serious Eye	0		STOT - Single Exposure	0	
Damage/Irritation Respiratory or Skin				~	
sensitisation	•		STOT - Repeated Exposure	0	
Mutagenicity	0		Legend:	– Data requirec – Data availabl – Data Not Ava	l to make classification available e but does not fill the criteria for classification ilable to make classification
CARCINOGEN	isopropanol	US Environmental Defense Scorecard Sus	spected Carcinogens		
CARONOULN					1
EYE	isopropanol	US - California OEHHA/ARB - Acute Refe (RELs) - Eye	rence Exposure Levels and Target	Organs	ISOPROPYL ALCOHOL (Isopropanol) X

Page 8 of 9

Nitrate CHEMets & Vacu-vials Ampoules, Nitrite CHEMets & VACUettes Refills and Vacu-vials Ampoules

RESPIRATORY

 ethylene glycol
 US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs) - Respiratory
 X

 isopropanol
 US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs) - Respiratory
 X

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Harmful to aquatic organisms.

For Ethylene Glycol: Log Kow: -1.93 to -1.36; Half-life (hr) air: 24 hrs; Henry \diamond s Law Constant: 1.41 \diamond 10-3 or 6.08 \diamond 10-3 Pa.m3/mol, (depending on method of calculation); Henry's atm m3 /mol: 2.3x10 atm-m/mol; Vapor Pressure: 7.9 Pa @ 20 C; BOD 5: 0.15 to 0.81, 12%; COD: 1.21 to 1.29; ThOD: 1.26; BCF: 10 to190.

Atmospheric Fate: In the atmosphere, ethylene glycol exists mainly in the vapor phase. It is degraded by reactions with hydroxyl radicals, (estimated half-life 24-50 hours). Direct breakdown of the substance by sunlight is not expected.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
water	LOW	LOW
ethylene glycol	LOW (Half-life = 24 days)	LOW (Half-life = 3.46 days)
isopropanol	LOW (Half-life = 14 days)	LOW (Half-life = 3 days)
gentisic acid	LOW	LOW
chromotropic acid disodium salt dihydrate	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
water	LOW (LogKOW = -1.38)
ethylene glycol	LOW (BCF = 200)
isopropanol	LOW (LogKOW = 0.05)
gentisic acid	LOW (LogKOW = 1.74)
chromotropic acid disodium salt dihydrate	LOW (LogKOW = -1.8968)

Mobility in soil

Ingredient	Mobility
water	LOW (KOC = 14.3)
ethylene glycol	HIGH (KOC = 1)
isopropanol	HIGH (KOC = 1.06)
gentisic acid	LOW (KOC = 38.81)
chromotropic acid disodium salt dihydrate	LOW (KOC = 2558)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product /	Packaging
	disposal

Dispose of according to federal, state, and local regulations.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant

NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source	Ingredient	Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	ethylene glycol	Y

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

water(7732-18-5) is found	
on the following regulatory	"US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"

Nitrate CHEMets & Vacu-vials Ampoules, Nitrite CHEMets & VACUettes Refills and Vacu-vials Ampoules

lists	
ethylene glycol(107-21-1) is found on the following regulatory lists	"US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)","US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants","US - Hawaii Air Contaminant Limits","US - California Permissible Exposure Limits for Chemical Contaminants","US ACGIH Threshold Limit Values (TLV) - Carcinogens","US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants","US - Oregon Permissible Exposure Limits (Z-1)","US - Michigan Exposure Limits for Air Contaminants","US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values","US NIOSH Recommended Exposure Limits (RELs)","US - Alaska Limits for Air Contaminants","US - Washington Permissible exposure limits of air contaminants","US ACGIH Threshold Limit Values (TLV) - Notice of Intended Changes","US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants","US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)","US ACGIH Threshold Limit Values (TLV)","US - Vermont Permissible Exposure Limits for Air Contaminants","US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"
isopropanol(67-63-0) is found on the following regulatory lists	"US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US - Idaho - Limits for Air Contaminants", "US - Hawaii Air Contaminant Limits", "US - California Permissible Exposure Limits for Chemical Contaminants", "US ACGIH Threshold Limit Values (TLV) - Carcinogens", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US - Oregon Permissible Exposure Limits (Z-1)", "US - Michigan Exposure Limits for Air Contaminants", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values", "US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)", "US NIOSH Recommended Exposure Limits (RELs)", "US - Alaska Limits for Air Contaminants", "US - Washington Permissible exposure Limits of air contaminants", "US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants", "US - Maniesota Permissible Exposure Limits (PELs)", "US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US - California OEHHA/RB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US - California OEHHA/RB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US - California OEHHA/RB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US - Colifornia OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US - Colifornia OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US - Colifornia OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US Coxic Substances Control Act (TSCA) - Chemical Substance Inventory", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US OSHA Permissible Exposure Levels (PELs) - Table Z1"
sulfanilic acid, sodium salt(123333-70-0) is found on the following regulatory lists	"US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"
gentisic acid(490-79-9) is found on the following regulatory lists	"US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"
chromotropic acid disodium salt dihydrate(5808-22-0) is found on the following regulatory lists	"US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"
CDTA, disodium magnesium salt(63451-33-2) is found on the following regulatory lists	"US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"
Proprietary ingredients() is found on the following regulatory lists	"Not Applicable"

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
Not Available	Not Available
Not Available	Not Available

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.



Simplicity in Water Analysis

Cover Page for Safety Data Sheet

Thank you for choosing CHEMetrics, Inc. We appreciate your business. In order to best serve your needs for accurate and complete Safety Data, we offer the following information as supplemental to the attached SDS.

SDS No.: S6900

Version No.: 3.2

Product Name: Cadmium Foil Packs for Nitrate CHEMets® Refills & Kits and Vacu-vials® Kits

Components of Water Analysis Products: R-6902, K-6903, K-6904, R-6904, R-6909, K-6909A, K-6909B, K-6909C, K-6909D, K-6923, K-6933

Product Descriptions:

Cadmium Foil Packs: Each foil pack contains approximately 0.3 g of solid. Each refill and test kit contains 30 foil packs.

Addendum to Section 14 Transport Information:

Shipping container markings and labels for this product, as received, may vary from the contents of section 14 of the SDS for one or both of the following reasons:

- CHEMetrics has packaged this product as Dangerous Goods in Excepted Quantities according to IATA, US DOT, and IMDG regulations.
- CHEMetrics has packaged this product as part of a test kit or reagent set composed of various chemical reagents and elected to ship as UN 3316 Chemical Kit, Hazard Class 9, Packing Group II or III.

In case of reshipment, it is the responsibility of the shipper to determine appropriate labels and markings in accordance with applicable transportation regulations.

Additional Information:

- "Print Date" = Revision Date (expressed as DD/MM/YYY)
- Test kits and reagents sets may contain additional chemical reagents. See separate SDS(s).

CHEMets®, VACUettes®, Vacu-vials®, and Titrets® are registered trademarks of CHEMetrics Inc.



CHEMetrics, Inc. Chemwatch: 9-123790 SDS No: S6900 Version No: 3.2 Safety Data Sheet according to OSHA HazCom Standard (2012) requirements Chemwatch Hazard Alert Code: 4 Issue Date: 29/06/2015 Print Date: 06/07/2015 Initial Date: 25/11/2014 S.GHS.USA.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Cadmium Foil Packs for Nitrate CHEMets Refills & Kits, and Vacu-vials Kits
Not Available
Not Applicable
Not Applicable
Not Available
Not Applicable

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Component of water analysis products R-6902, K-6903, K-6904, R-6904, R-6909, K-6909A, K-6909B, K-6909D, K-6909D, K-6923, K-6933

Details of the manufacturer/importer

Registered company name	CHEMetrics, Inc.
Address	4295 Catlett Road, Midland, VA. 22728 United States
Telephone	1-540-788-9026
Fax	1-540-788-4856
Website	www.chemetrics.com
Email	technical@chemetrics.com

Emergency telephone number

Association / Organisation	ChemTel Inc.
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	+01-813-248-0585

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

GHS Classification	Acute Toxicity (Inhalation) Category 2, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A, STOT - SE (Resp. Irr.) Category 3, Germ Cell Mutagen Category 2, Carcinogen Category 1B, Reproductive Toxicity Category 1B, STOT - RE Category 1, Acute Aquatic Hazard Category 2, Chronic Aquatic Hazard Category 2		
Label elements			
GHS label elements			
SIGNAL WORD	DANGER		
Hazard statement(s)			
H330	Fatal if inhaled		
H315	Causes skin irritation		
H319	Causes serious eye irritation		
H335	May cause respiratory irritation		
H341	Suspected of causing genetic defects		

H350	May cause cancer	
H360	May damage fertility or the unborn child	
H372	Causes damage to organs through prolonged or repeated exposure	
H401	Toxic to aquatic life	
H411	Toxic to aquatic life with long lasting effects	

Precautionary statement(s) Prevention

• •	
P201	Obtain special instructions before use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P281	Use personal protective equipment as required.
P270	Do not eat, drink or smoke when using this product.

Precautionary statement(s) Response

P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P308+P313	IF exposed or concerned: Get medical advice/attention.	
P310	Immediately call a POISON CENTER/doctor/physician/first aider	
P362	Take off contaminated clothing.	
P305+P351+P338	8 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	

Precautionary statement(s) Storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
P405	Store locked up.	

Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
87-69-4	25-35	tartaric acid
7757-82-6	20-30	sodium sulfate
868-18-8	15-25	sodium tartrate
36679-96-6	5-15	cyclohexanediaminetetraacetic acid, trisodium salt
7487-88-9	5-15	magnesium sulfate, anhydrous
7440-43-9	1-10	cadmium
19332-78-6	<0.5	CDTA copper salt
35429-19-7	<0.1	Polyquaternium 15

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. Do NOT attempt to remove particles attached to or embedded in eye . Lay victim down, on stretcher if available and pad BOTH eyes, make sure dressing does not press on the injured eye by placing thick pads under dressing, above and below the eye.
Skin Contact	 If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

		5	Brint Data: 06/07/201
/	Cadmium Foil Packs for Nitrate CHE	EMets Refills & Kits, and Vacu-vial	s Kits
	Transport to hospital, or doctor, without delay.		
	 Immediately give a glass of water. 		
Ingestion	► First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.		
Most important symptoms	and effects, both acute and delayed		
	See Section 11		
Indication of any immedia	te medical attention and special treatmen	t needed	
 Treat symptomatically. High acute exposure, to cac For acute inhalations, initial post-exposure. Respiratory f For acute oral exposures, g; If vomiting is not prominent, CaNa2EDTA is the chelator 	mium, produces delayed pulmonary oedema progressing presentation simulates metal fume fever (fever, headache ailure may ensue in 3-10 days. astroenteritis results with sudden onset of vomiting, diarrh use Ipecac/lavage/catharsis in usual manner. of choice for acute cadmium exposure. British Anti-Lewis	g to interstitial fibrosis. e, dyspnoea, pleuritic chest pain, conjunctivitis, rhinitis oea and abdominal pain. site increases nephrotoxicity and therefore is not indic	s, sore throat, cough) developing 4-12 hours cated
[Ellenhorn and Barceloux: Medic	al Toxicology]		
COMMENTS on HUMAN TOX	ICITY:		
- Between 10 and 50% of inhale	d cadmium is adsorbed, the adsorption being greater for	smaller particles and fumes; absorption through skir	n is negligible.
- The half-life of cadmium in the	numan body is thought to be about around 30 years and it	has no known biological function.	
Blood and urine cadmium conce Normal concentrations Blood <27 nml/l (<3ug/l), non-sn <54 nmol/l (<6 ug/l), smokers Urine <18 nmol/l (<2 ug/l), non-sn 0.4-1.3 nmol/mmol creatinine <45 nmol/l (<5 ug/l), smokers 10-35 nmol/mmol creatinine	ntrations may be determined. nokers smokers	Hazardous concentrations >180 nmol/l (>20 ug/l) >180 nmol/l (>20 ug/l) >4-13 nmol/mmol creatinin	ie
BIOLOGICAL EXPOSURE IND	EX (BEI)		
These represent the determinan	ts observed in specimens collected from a healthy worker	exposed at the Exposure Standard (ES or TLV):	
Determinant	Sampling time	Index	Comments
Cadmium in urine	Not critical	5 ug/g creatinine	В
Cadmium in blood	Not critical	5 ug/L	В
B: Background levels occur in sp	ecimens collected from subjects NOT exposed		
SECTION 5 FIREFIGHTIN	IG MEASURES		
Extinguishing media			
	Metal dust fires need to be smothered with sand inert	dry powders	
	DO NOT USE WATER, CO2 or FOAM.	ary powders.	
	 Use DRY sand, graphite powder, dry sodium chl 	oride based extinguishers, G-1 or Met L-X to smothe	er fire.
	 Confining or smothering material is preferable to Chemical reaction with CO2 may produce flamma 	applying water as chemical reaction may produce fla ble and explosive methane.	mmable and explosive hydrogen gas.
Special hazards arising fr	om the substrate or mixture		
Fire Incompatibility	 Avoid contamination with oxidising agents i.e. nit 	rates, oxidising acids, chlorine bleaches, pool chlorin	e etc. as ignition may result
Advice for firefighters	*		
	Alert Fire Brigade and tell them location and set	ire of bazard	
Fire Fighting	Vertice in the index of the intermited with all that Wear breathing apparatus plus protective gloves Prevent, by any means available, spillage from et Use fire fighting procedures suitable for surroun	in the event of a fire. Itering drains or water courses. ding area.	

- ▶ DO NOT approach containers suspected to be hot.
- DO NOT disturb burning dust. Explosion may result if dust is stirred into a cloud, by providing oxygen to a large surface of hot metal. • DO NOT use water or foam as generation of explosive hydrogen may result.
- Fire/Explosion Hazard With the exception of the metals that burn in contact with air or water (for example, sodium), masses of combustible metals do not represent unusual fire risks because they have the ability to conduct heat away from hot spots so efficiently that the heat of combustion cannot be maintained - this means that it will require a lot of heat to ignite a mass of combustible metal. Generally, metal fire risks exist when sawdust, machine shavings and other metal 'fines' are present.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	 Clean up waste regularly and abnormal spills immediately. Avoid breathing dust and contact with skin and eyes. Wear protective clothing, gloves, safety glasses and dust respirator. Use dry clean up procedures and avoid generating dust. Vacuum up or sweep up.
--------------	--

Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by all means available, spillage from entering drains or water courses. Consider evacuation (or protect in place).
	Personal Protective Equipment advice is contained in Section 8 of the MSDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	For molten metals: Molten metal and water can be an explosive combination. The risk is greatest when there is sufficient molten metal to entrap or seal off water. Water and other forms of contamination on or contained in scrap or remelt ingot are known to have caused explosions in melting operations. While the products may have minimal surface roughness and internal voids, there remains the possibility of moisture contamination or entrapment. If confined, even a few drops can lead to violent explosions. Wear impact- and splash-resistant eyewear.
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry area protected from environmental extremes. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. For optimum analytical performance, store in the dark and at room temperature.

Conditions for safe storage, including any incompatibilities

Suitable container	Bulk bags: Reinforced bags required for dense materials.
Storage incompatibility	 Many metals may incandesce, react violently, ignite or react explosively upon addition of concentrated nitric acid. Avoid reaction with oxidising agents, bases and strong reducing agents. Metals exhibit varying degrees of activity. Reaction is reduced in the massive form (sheet, rod, or drop), compared with finely divided forms. The less active metals will not burn in air but: can react exothermically with oxidising acids to form noxious gases.

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	cadmium	Cadmium	0.005 mg/m3	Not Available	Not Available	see 1910.1027;(as Cd)
US OSHA Permissible Exposure Levels (PELs) - Table Z2	cadmium	Cadmium fume / Cadmium dust	0.1 mg/m3 / 0.2 mg/m3	Not Available	0.3 mg/m3 / 0.6 mg/m3	(Z37.5–1970);This standard applies to any operations or sectors for which the Cadmium standard, 1910.1027, is stayed or otherwise not in effect
US ACGIH Threshold Limit Values (TLV)	cadmium	Cadmium	0.01 mg/m3	Not Available	Not Available	TLV® Basis: Kidney dam; BEI
US NIOSH Recommended Exposure Limits (RELs)	cadmium	Cadmium metal: Cadmium	Not Available	Not Available	Not Available	Ca See Appendix A [*Note: The REL applies to all Cadmium compounds (as Cd).]

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
tartaric acid	Tartaric acid	1.6 mg/m3	17 mg/m3	100 mg/m3
sodium sulfate	Sodium sulfate, anhydrous	11 mg/m3	130 mg/m3	650 mg/m3
sodium tartrate	Sodium tartrate dihydrate	3.9 mg/m3	43 mg/m3	260 mg/m3
magnesium sulfate, anhydrous	Magnesium sulfate (1:1)	0.18 mg/m3	2 mg/m3	160 mg/m3
cadmium	Cadmium	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
tartaric acid	Not Available	Not Available
sodium sulfate	Not Available	Not Available
sodium tartrate	Not Available	Not Available
cyclohexanediaminetetraacetic acid, trisodium salt	Not Available	Not Available
magnesium sulfate, anhydrous	Not Available	Not Available
cadmium	50 mg/m3 / 9 mg/m3	9 mg/m3 / 9 [Unch] mg/m3
CDTA copper salt	Not Available	Not Available

Page 5 of 8

Cadmium Foil Packs for Nitrate CHEMets Refills & Kits, and Vacu-vials Kits

Polyquaternium 15	Not Available	Not Available	
Exposure controls			
Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier to effective in protecting workers and will typically be independent of work The basic types of engineering controls are: Process controls which involve changing the way a job activity or proc Enclosure and/or isolation of emission source which keeps a selected "removes" air in the work environment. Ventilation can remove or dilute	vetween the worker and the hazard. Well-designed engineering controls can be highly ker interactions to provide this high level of protection. ess is done to reduce the risk. hazard "physically" away from the worker and ventilation that strategically "adds" and e an air contaminant if designed properly.	
Personal protection			
Eye and face protection	 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses m lenses or restrictions on use, should be created for each workplac chemicals in use and an account of injury experience. 	ay absorb and concentrate irritants. A written policy document, describing the wearing of the or task. This should include a review of lens absorption and adsorption for the class of	
Skin protection	See Hand protection below		
Hands/feet protection	The selection of solitable gloves does not only depend on the material, but also on number marks of quality which vary norm manufacture to manufacture. When the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: Frequency and duration of contact, chemical resistance of glove material, glove thickness and dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).		
Body protection	See Other protection below		
Other protection	 Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted. [AS/NZS or national equivalent] Emergency deluge showers and eyewash fountains, supplied with potable water, should be located near, within sight of, and on the same level with locat where direct exposure is likely. Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purpose: decomparison or discoveral 		
Thermal hazards	Not Available		

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computergenerated** selection:

Cadmium Foil Packs for Nitrate CHEMets Refills & Kits, and Vacu-vials Kits Not Available

|--|

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise

be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Particulate. (AS/NZS 1716 & 1715, EN 143:000 & 149:001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	-	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

* - Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Blue metallic powder		
Physical state	Solid	Relative density (Water = 1)	Not Available
Odour	Odourless	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available

Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Partly miscible	pH as a solution	3.4
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Inhalation of dusts, generated by the material, during the course of normal har The material can cause respiratory irritation in some persons. The body's res	dling, may produce severely toxic effects; these may be fatal. ponse to such irritation can cause further lung damage.
Ingestion	The material is not thought to produce adverse health effects following ingest systemic effects have been produced following exposure of animals by at leas minimum. Magnesium salts are generally absorbed so slowly that swallowing these cau removed (for example in bowel obstruction or paralysis), it may irritate the gut Side effects of magnesium salts include upset stomach, dry mouth, dry nose, and nose.	ion (as classified by EC Directives using animal models). Nevertheless, adverse t one other route and good hygiene practice requires that exposure be kept to a use few toxic effects, with purging being the most significant. If it cannot be lining and be absorbed into the body. dry throat, drowsiness, nausea, heartburn, and thickening of the lining of the throat
Skin Contact	Skin contact with the material may be harmful; systemic effects may result folk This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, r of the material and ensure that any external damage is suitably protected.	owing absorption. nay produce systemic injury with harmful effects. Examine the skin prior to the use
Eye	This material can cause eye irritation and damage in some persons. Solutions	s of low-molecular weight organic acids cause pain and injury to the eyes.
Chronic	Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Strong evidence exists that this substance may cause irreversible mutations (though not lethal) even following a single exposure. There is ample evidence that this material can be regarded as being able to cause cancer in humans based on experiments and other information. Toxic: danger of serious damage to health by prolonged exposure through inhalation and if swallowed. This material can cause serious damage if one is exposed to it for long periods.	
Cadmium Foil Packs for Nitrate CHEMets Refills & Kits, and Vacu-vials Kits	ΤΟΧΙΟΙΤΥ	IRRITATION
Cadmium Foil Packs for Nitrate CHEMets Refills & Kits, and Vacu-vials Kits	ΤΟΧΙΟΙΤΥ	IRRITATION

TARTARIC ACID	Convulsions, haemorrhage recorded.
SODIUM SULFATE	Equivocal Tumorigen by RTECS criteria. Reproductive effector in mice.
MAGNESIUM SULFATE, ANHYDROUS	Intravenous (woman) LDLo: 80 mg/kg/2m-I
POLYQUATERNIUM 15	The lubricant Polyquaternium 15 not only damaged the rectal lining cells in tissue culture but appeared actively to increase HIV replication in the cell cultures. Polyquaternium-15, a commonly-used cosmetic ingredient has the property of facilitating HIV's attachment to cells.

Cadmium Foil Packs for Nitrate CHEMets Refills & Kits, and Vacu-vials Kits & TARTARIC ACID & SODIUM SULFATE

CYCLOHEXANEDIAMINETETRAACETIC ACID, TRISODIUM SALT & CDTA COPPER SALT Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance.

No significant acute toxicological data identified in literature search.

Acute Toxicity	*	Carcinogenicity	¥
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	*
Mutagenicity	×	Aspiration Hazard	0
		Legend: 🗸	Data required to make classification available

– Data required to make classification available
 N – Data available but does not fill the criteria for classification
 N – Data Not Available to make classification

CMR STATUS

Not Applicable

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites. For Metal:

Atmospheric Fate - Metal-containing inorganic substances generally have negligible vapour pressure and are not expected to partition to air.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
tartaric acid	LOW	LOW
sodium sulfate	HIGH	HIGH
magnesium sulfate, anhydrous	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
tartaric acid	LOW (LogKOW = -1.0017)
sodium sulfate	LOW (LogKOW = -2.2002)
magnesium sulfate, anhydrous	LOW (LogKOW = -2.2002)

Mobility in soil

Ingredient	Mobility
tartaric acid	HIGH (KOC = 1)
sodium sulfate	LOW (KOC = 6.124)
magnesium sulfate, anhydrous	LOW (KOC = 6.124)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

Dispose of according to federal, state, and local regulations.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant



end of SDS

Cadmium Foil Packs for Nitrate CHEMets Refills & Kits, and Vacu-vials Kits

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture tartaric acid(87-69-4) is found "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory" on the following regulatory lists sodium sulfate(7757-82-6) is "US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)", "US - Washington Toxic air pollutants and their ASIL, SQER found on the following and de minimis emission values", "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory" regulatory lists sodium tartrate(868-18-8) is found on the following "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory' regulatory lists cyclohexanediaminetetraacetic acid. trisodium "Not Applicable" salt(36679-96-6) is found on the following regulatory lists magnesium sulfate. anhydrous(7487-88-9) is "US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)", "US Toxic Substances Control Act (TSCA) - Chemical found on the following Substance Inventory regulatory lists "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "US - Alaska Limits for Air Contaminants", "US -California - Proposition 65 - Priority List for the Development of MADLs for Chemicals Causing Reproductive Toxicity", "US - California OEHHA/ARB -Chronic Reference Exposure Levels and Target Organs (CRELs)", "US - California Permissible Exposure Limits for Chemical Contaminants", "US -California Proposition 65 - Carcinogens", "US - California Proposition 65 - Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity", "US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens", "US - California Proposition 65 - Reproductive Toxicity", "US - Hawaii Air Contaminant Limits", "US - Idaho - Acceptable Maximum Peak Concentrations", "US - Idaho - Limits for Air Contaminants", "US -Michigan Exposure Limits for Air Contaminants", "US - Minnesota Permissible Exposure Limits (PELs)", "US - New Jersey Right to Know - Special Health cadmium(7440-43-9) is found Hazard Substance List (SHHSL): Carcinogens", "US - Oregon Permissible Exposure Limits (Z-1)", "US - Oregon Permissible Exposure Limits (Z-2)", "US on the following regulatory Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US - Washington Permissible exposure lists limits of air contaminants", "US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US - Wyoming Toxic and Hazardous Substances Table Z-2 Acceptable ceiling concentration, Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift","US ACGIH Threshold Limit Values (TLV)", "US ACGIH Threshold Limit Values (TLV) - Carcinogens", "US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)", "US EPA Carcinogens Listing", "US EPCRA Section 313 Chemical List", "US National Toxicology Program (NTP) 13th Report Part A Known to be Human Carcinogenes", "US NIOSH Recommended Exposure Limits (RELs)", "US OSHA Carcinogens Listing", "US OSHA Permissible Exposure Levels (PELs) - Table Z1", "US OSHA Permissible Exposure Levels (PELs) - Table Z2","US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory "US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)", "US - Hawaii Air Contaminant Limits", "US - Idaho - Limits CDTA copper salt(19332-78-6) for Air Contaminants", "US - Minnesota Permissible Exposure Limits (PELs)", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for is found on the following Air Contaminants", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US - Washington Toxic air pollutants regulatory lists and their ASIL, SQER and de minimis emission values", "US OSHA Permissible Exposure Levels (PELs) - Table Z1", "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory Polyquaternium 15(35429-19-7) is found on the "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory' following regulatory lists

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
Not Available	Not Available
Not Available	Not Available
Not Available	Not Available

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chernwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at: www.chemwatch.net

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.